

<b>BD Loops Preformed Saw-Cut Loops</b>		
Save up to: <b>55 Minutes Per Loop</b>	Time Saved	Time Saving Features:
	15min	Don't have to wrap the loop in the field.
	10min	Don't have to twist the lead-in wires.
	10min	Don't have to make a wider saw-cut for twisted lead-in, entire loop and lead-in fits into a 3/16" or 1/4" saw-cut groove.
	5min	Don't have to use backer-rod ( BD Loops preformed loops have backer-rod built into the wire)
15min	Seal saw-cut loops in 1 pass by using BD Loops 3/16" sealant applicator tip. (our modified applicator tips come with each tube of BD-LG)	

*Saw-Cut Loops* are used for saw-cut installations where a 3/16" groove is cut into the concrete or asphalt and the wire is stuffed and sealed (using loop sealant) into the groove. Custom polyethylene outer jacket protects a micro-dusted nylon coated inner jacketed 16AWG stranded wire. The saw-cut loop has a built in backer-rod securely fitting a 3/16" saw-cut groove eliminating the need to apply backer-rod to hold the loop to the bottom of the saw-cut groove and requires 25-40% less loop sealant to seal the groove. The entire loop including the lead-in fits within a 3/16" or 1/4" saw-cut groove preventing wasted time spent double saw-cutting or doubling blades to cut the home run lead-in.

<b>Additional Advantages of BD Loops Preformed Saw-Cut Loop</b>
<ul style="list-style-type: none"> <li>You do not have to cut an exact pattern for our saw-cut loops. You can make the loops smaller using a simple trick. Visit <b>BD Loops.com</b> for more information.</li> <li>Save 25-40% on loop sealant because of built in backer-rod sealing the bottom portion of the saw-cut groove.</li> <li>16AWG wire is used, twice as much copper per foot as the commonly used 18AWG wire. Resulting in a better quality/performing loop.</li> <li>Easy to follow instructions packaged with every loop.</li> <li>Reliability of BD Loops, each loop is tested 3 different ways at the factory; our dedication to quality has allowed us to sell preformed loops for over 15 years providing reliable products.</li> <li>Pre-phased at the factory.</li> </ul>

<b>BD Loops Preformed Direct Burial Loops</b>		
Save up to: <b>45 Minutes Per Loop</b>	Time Saved	Time Saving Features:
	5min	Easy To Shape
	10min	Jacketed lead-in, don't have to twist the lead-in wires.
	5min	Easy to unwrap, loop is folded at half-way point and does not coil back.
	10min	Loop is packaged as a kit. Cable ties and labels are included.
15min	Flex Yoke allows you to easily readjust the angle of the lead-in run without having to reposition entire loop. Yoke has 1/2" coupler to easily attach 1/2" PVC for a water tight seal.	

*Direct Burial Loops* are used for installations in concrete, under asphalt, pavers, or gravel roads. The most common installation is the loop tied directly to the rebar before concrete is poured. Wire is rated for direct burial and designed for a direct burial application. Unlike loops wrapped through PVC, The BD Loop does not have an air pocket resulting in fewer repeat service calls due to phantom detections caused by ground vibration. Built with a high quality solid 16AWG wire out performing other preformed loops with twice as much copper per foot allowing better detections. Solid 16AWG wire also results in the loop being very ridged giving the installer the opportunity to easily set-up and layout the loop and prevents the loop from falling in-between the rebar patten. Twisted jacketed lead-in prevents "coil back" from normal twisted lead-in, preventing wasted time untangling lead-in wires. The loop wire has arrows indicating the direction of current allowing easy understanding of phasing. Each loop comes with an installation kit including easy-to-understand instructions, cable ties for installation on top of rebar, and stickers for easy identification after the loops have been installed.

<b>Additional Advantages of BD Loops Preformed Direct Burial Loop</b>
<ul style="list-style-type: none"> <li>Don't have to wrap the loop in the field.</li> <li>Packaged as a kit.</li> <li>16AWG solid wire is used, 2x as much copper as the commonly used 18AWG wire. Resulting in a better quality/performing loop.</li> <li>Superior designed loop to fit the application:             <ul style="list-style-type: none"> <li>No Air-Pocket</li> <li>Easy to reposition flex yoke with 1/2" coupler.</li> <li>Easy to form, very ridged.</li> <li>Direct Burial rated wire.</li> </ul> </li> <li>Easy to follow instructions packaged with every loop.</li> <li>Reliability of BD Loops, each loop is tested 3 different ways at the factory; our dedication to quality has allowed us to sell preformed loops for over 15 years providing reliable products.</li> <li>Pre-phased at the factory.</li> </ul>

# BD Loops

## Direct Burial Preformed Loop

To be installed in a concrete pour, gravel road, under asphalt, and pavers.



Loop Kit Includes:  
4-6 cable ties  
3 lead-in-loop labels

Install the highest quality loop, save time, and reduce service calls by using a BD Loops preformed loop.

Custom sizes are available and ship same day! (For orders placed before 12:30pm PST.)


Learn more about our Direct Burial Loops Online at: [www.BDLoops.com](http://www.BDLoops.com).



Driveway Width/ Vehicle Type		Recommended Loop Size		BD Loops part #		
Residential	Commercial	Residential	Commercial	40ft Lead-in	60ft Lead-in	100ft Lead-in
8-10ft	N/A	2½x3½ or 3x3	-	RL 12-40	EL 12-60	-
8-10ft	N/A	2½x4½ or 3x4	-	RL 14-40	EL 14-60	-
8-10ft	N/A	4x4 or 3x5	-	RL 16-40	EL 16-60	-
9ft	N/A	4x5 or 3x6	-	RL 18-40	EL 18-60	-
10ft	N/A	4x6 or 3x8	-	RL 20-40	EL 20-60	-
12ft	10ft	4x8	6x6	RL 24-40	EL 24-60	EL 24-100
14ft	12ft	4x10	6x8	-	EL 28-60	EL 28-100
16ft	14ft	4x12	6x10	RL 32-40	EL 32-60	EL 32-100
-	16ft	-	6x12	RL 36-40	EL 36-60	EL 36-100
-	18ft	-	6x14	-	EL 40-60	EL 40-100
-	20ft	-	6x16	RL 44-40	EL 44-60	EL 44-100
-	24ft	-	6x20	RL 52-40	EL 52-60	EL 52-100

# BD Loops

## Preformed 3/16 Saw-Cut Loop



Save Time, Money, and Material with BD Loops Preformed Saw-Cut Loops!

Custom Sizes are available and ship same day! (For orders placed before 12:30pm PST.)

Learn more about our Saw-Cut Loops Online at: [www.BDLoops.com](http://www.BDLoops.com)



Driveway Width/ Vehicle Type		Recommended Loop Size		BD Loops part #		
Residential	Commercial	Residential	Commercial	20ft Lead-in	50ft Lead-in	100ft Lead-in
8-10ft	N/A	2½x3½ or 3x3	-	SC 12-20	SC 12-50	-
8-10ft	N/A	2½x4½ or 3x4	-	SC 14-20	SC 14-50	-
8-10ft	N/A	4x4 or 3x5	-	SC 16-20	SC 16-50	-
9ft	N/A	4x5 or 3x6	-	SC 18-20	SC 18-50	-
10ft	N/A	4x6 or 3x8	-	SC 20-20	SC 20-50	-
12ft	10ft	4x8	6x6	SC 24-20	SC 24-50	SC 24-100
14ft	12ft	4x10	6x8	-	SC 28-50	SC 28-100
16ft	14ft	4x12	6x10	SC 32-20	SC 32-50	SC 32-100
-	16ft	-	6x12	SC 36-20	SC 36-50	SC 36-100
-	18ft	-	6x14	-	SC 40-50	SC 40-100
-	20ft	-	6x16	SC 44-20	SC 44-50	SC 44-100
-	24ft	-	6x20	SC 52-20	SC 52-50	SC 52-100